

# LI Compact Fluorescent Lamps

With our growing portfolio of dedicated lamps we can offer a variety of options providing a sophisticated choice for luminaire design.

Our LI lamps offer up to 80% energy saving and have a very long life - up to 8000 hours and more.

They have a minimum efficiency of 45 lm/w and comply with parts L1 and L2 of the building regulations.

All of our fittings come supplied with lamps.

Currently no dimming options are available.



**2312**  
L-1 Tube Tip  
9w

**2317**  
L-1 Tube  
9w

**2315**  
L-1 GLS  
15w



**2310**  
L-1 Candle  
9w



**2313**  
L-1 Micro  
9w



**2318**  
L-1 Spot  
11w



**2319**  
L-1 IP44 Spot  
11w



**2840**  
L-1 Spiral spot  
10w



**2842**  
L-1 Spiral  
10w

**2841**

Reflector for 2842

Code No.	Type	Voltage (v)	Watts (w)	Lumen	Colour Temp (K)	Life Time (h)	Overall Length (mm)	Max Width (mm)	RoHS	CE	EU Energy Rating	Watertight Lamp	Integrated Electronic Start
tp24 - 2310	L-1 Candle	220/240	9	405	2700K warm white	8,000	105	39	✓	✓	A	✓	✓
tp24 - 2312	L-1 Tube Tip	220/240	9	420	2700K warm white	8,000	152	31	✓	✓	A	✓	✓
tp24 - 2313	L-1 Micro	220/240	9	405	2700K warm white	8,000	78	48	✓	✓	A	✗	✓
tp24 - 2315	L-1 GLS	220/240	15	820	2700K warm white	8,000	130	65	✓	✓	A	✗	✓
tp24 - 2317	L-1 Tube	220/240	9	450	2700K warm white	8,000	131	31	✓	✓	A	✓	✓
tp24 - 2318	L-1 Spot	220/240	11	300*/475**	3000K warm white	10,000	76	50	✓	✓	B	✗	✓
tp24 - 2319	L-1 Spot IP	220/240	11	300*/475**	3000K warm white	10,000	76	50	✓	✓	B	✓	✓
tp24 - 2840	L-1 Spiral spot	220/240	10	470**	3000K warm white	8,000	74	52	✓	✓	A	✗	✓
tp24 - 2842	L-1 Spiral	220/240	10	470	3000K warm white	8,000	71	39	✓	✓	A	✗	✓

\* Measured in sphere with reflector \*\* Measured in sphere without reflector